

LUBRICANT

Item		Capacity			Classification
		Liters	US qts	Imp. qts	
Manual transaxle oil	C52	2.6	2.7	2.3	API GL-4 or GL-5 SAE 75W-90
	E150F	5.2	5.5	4.6	API GL-5 Viscosity: Above -18°C (0°F) SAE90 Below -18°C (0°F) SAE80W
Automatic transaxle fluid					ATF DEXRON® II
A241 E	Dry fill	8.0	8.5	7.0	
	Drain and refill	3.3	3.5	2.9	
A243L	Dry fill	7.7	8.1	6.8	
	Drain and refill	3.3	3.5	2.9	
Differential oil		1.1	1.2	1.0	API GL-5 Hypoid gear oil Viscosity: Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE80W-90
Power steering fluid	Total	0.8	0.85	0.70	ATF DEXRON® II
Brake fluid		—			SAE J1703 or FMVSS No. 116 DOT3

LUBRICANT

Item			Capacity			Classification
			Liters	U S qts	Imp. qts	
Engine oil	4A-FE	Dry fill	3.7	3.9	3.3	API grade SG, multigrade fuel-efficient and recommended viscosity oil
		Drain and refill				
		w/ Oil filter change	3.2	3.3	2.8	
		w/o Oil filter change	3.0	3.1	2.6	
	3S-GTE	Dry fill	4.3	4.5	3.8	
		Drain and refill				
		w/ Oil filter change	3.9	4.1	3.4	
		w/o Oil filter change	3.6	3.8	3.2	
	5S-FE (w/ Oil cooler)	Dry fill	4.6	4.9	4.0	
		Drain and refill				
		w/ Oil filter change	4.2	4.4	3.7	
		w/o Oil filter change	3.8	4.0	3.3	
5S-FE (w/o Oil cooler)	Dry fill	4.5	4.8	4.0		
	Drain and refill					
	w/ Oil filter change	4.1	4.3	3.5		
	w/o Oil filter change	3.7	3.9	3.3		