

COOLING SYSTEM SPECIFICATIONS - 2.2L 4-CYL

1994 Toyota Celica

1994 ENGINE COOLING
Toyota Cooling System Specifications
Celica 2.2L 4-Cyl

SPECIFICATIONS

BELT ADJUSTMENT

Ensure belt tension is within specification. See appropriate BELT ADJUSTMENT table.

4-CYLINDER BELT ADJUSTMENT TABLE
Tension In Lbs. (kg) Using Burroughs Tension Gauge

Application	New Belt	(1) Used Belt
Celica		
2.2L (5S-FE)		
A/C	165 (75)	110 (50)
Alternator		
With A/C	165 (75)	110 (50)
Without A/C	125 (57)	95 (43)
Power Steering	125 (57)	80 (36)

(1) - Used belt is a belt in operation at least 5 minutes.

COOLING SYSTEM SPECIFICATIONS

4-CYLINDER COOLING SYSTEM SPECIFICATIONS TABLE

Application	Specification
Coolant Replacement Interval	
First Service Interval (1)	45,000 Miles Or 36 Months
Coolant Capacity	
Celica	
2.2L (5S-FE)	
A/T	7.5 Qts. (7.1L)
M/T	7.1 Qts. (6.7L)

(1) - After first service interval, replace coolant every 30,000 miles or 24 months.

COOLING SYSTEM BLEEDING

No special cooling system bleeding procedure is required.